

4.1 Ergebnistabelle Bestand													
Berechnung für Strömen													
Nummer	W[m]	He[m]	v-li	v-m	A-li	Q[m3/s]	Q-li	R[m]	t[m]	Ie	Fr-ges	S-m	X-li
Km	Pro-Int	Wgr[m]	v-fl	[m/s]	A-fl	gesamt	Q-fl	U[m]	max.	[o/oo]	Fr-fl	[N/m2]	X-re
Bezeichnung	ö/i/tgr	dW[m]	v-re	v2/2g	A-re	A[m2]	Q-re			ks-fl	Alpha		Wsp-B
1	445.28	445.73	0.00	2.95	0.0	9.6	0	0.0	0	12.1	1.0	0	12.02
0.0005		445.28	2.98		3.2		9.598	0.0	1.21		1.0	107	15.96
	tgr	0.00	0.03	0.45	0.0	3.3	0.001		0.16	0	1.0	9.3	3.94
2	445.44	445.84	0.02	2.73	0.0	9.6	0	0.0	0.05	9.8	1.0	0	10.93
0.008		445.44	2.85		3.3		9.428	0.0	1.26		1.0	85.4	15.82
	tgr	0.16	0.85	0.41	0.2	3.5	0.171		0.45	0	1.1	21.5	4.88
3	445.67	446.03	0.54	2.57	0.1	9.6	0.076	0.0	0.21	9.6	1.0	10	11.40
0.01677		445.67	2.65		3.6		9.523	0.0	1		1.0	72	17.41
	tgr	0.24	0.00	0.35	0.0	3.7	0		0	0	1.1	0	6.01
4	446.22	446.61	0.00	2.75	0.0	9.6	0	0.0	0	11.9	1.0	0	11.87
0.024557		446.22	2.75		3.5		9.6	0.0	1.14		1.0	89.3	16.42
	tgr	0.55	0.00	0.39	0.0	3.5	0		0	0	1.0	0	4.55
4.1	447.42	447.61	0.90	1.66	2.1	9.6	1.92	0.0	0.32	6.2	0.8	18.5	4.95
0.030357		0.00	2.10		3.7		7.68	0.0	2.03		0.5	123	13.75
		1.20	0.00	0.19	0.0	5.8	0		0	0	1.3	0	8.80
8	447.62	447.63	0.26	0.44	9.8	9.6	2.541	0.0	0.87	0.2	0.2	1.2	-5.07
0.047357		446.53	0.63		10.9		6.894	0.0	2.1		0.2	3.2	22.14
		0.20	0.14	0.02	1.2	21.9	0.164		0.51	0	1.6	0.5	27.21
9	447.61	447.67	0.01	1.14	0.0	9.6	0	0.0	0.03	1.3	0.4	0	13.18
0.081357		446.98	1.15		8.4		9.6	0.0	1.82		0.4	11.9	23.37
		-0.01	0.01	0.07	0.0	8.4	0		0	0	1.0	0	10.19
10	447.64	447.74	0.40	0.98	3.5	9.6	1.401	0.0	0.35	2.0	0.7	3.8	-2.76
0.087357		0.00	1.56		4.8		7.441	0.0	1.85		0.4	27	24.94
		0.03	0.49	0.10	1.6	9.8	0.757		0.5	0	2.0	5.2	27.70
11	447.74	447.75	0.30	0.42	11.2	9.6	3.372	0.0	0.84	0.3	0.2	1.5	-7.72
0.095357		447.12	0.62		9.0		5.648	0.0	1.86		0.2	3.2	26.88
		0.10	0.22	0.01	2.7	23.0	0.581		0.77	0	1.5	1	34.60
12	447.74	447.77	0.40	0.61	1.9	9.6	0.774	0.0	0.79	0.8	0.4	2.6	-1.47
0.128557		447.38	1.01		5.2		5.284	0.0	1.64		0.3	9	31.55
		0.00	0.42	0.03	8.5	15.7	3.543		0.73	0	1.7	3	33.02
13	447.88	447.99	0.00	1.43	0.0	9.6	0	0.0	0	5.4	0.8	0	-8.03
0.189857		447.76	1.51		6.3		9.444	0.0	1.35		0.9	14.8	19.72
		0.13	0.35	0.11	0.4	6.7	0.155		0.17	0	1.1	4.4	18.37
14	448.40	448.41	0.00	0.42	0.0	9.6	0	0.0	0	0.3	0.2	0	-9.03
0.197857		0.00	0.50		15.0		7.573	0.0	1.78		0.2	2.4	34.02
		0.52	0.25	0.01	8.0	23.0	2.027		0.66	0	1.2	1.2	43.05
15	448.40	448.41	0.00	0.51	0.0	9.6	0	0.0	0	0.6	0.3	0	-8.98
0.205857		447.88	0.58		15.0		8.653	0.0	1.8		0.2	3.4	32.45
		0.00	0.25	0.02	3.8	18.8	0.947		0.51	0	1.2	1.5	41.42
16	448.48	448.64	0.52	1.36	0.3	9.6	0.164	0.0	0.94	5.6	1.0	8.1	1.27
0.256857		448.48	1.88		4.3		8.082	0.0	1.46		0.7	37	26.68
	tgr	0.08	0.55	0.15	2.5	7.1	1.353		0.22	0	1.6	8.1	25.41